

PRODUCT INFORMATION SHEET

Pacific Acrylic Flat Finish

Pacific Acrylic Flat Finish is the class paint for those beautiful interiors & exteriors of a dream-home. Based on 100% acrylic emulsion, it is highly resistant to alkalis and fungus etc. Its superior flow property eliminates brush marks and yields smooth levelled finish. Available in mood creating shades, 100% Acrylic Flat Finish dries fast, and is perfectly washable to give the walls the freshly-painted look year after year. Ideal for ceilings.

TECHNICAL DATA

AREAS OF APPLICATION	Plaster, masonry, hardboards, plywood, etc.
SUPPLY VISCOSITY	Ready for use, brushing and rolling. (For spraying reduce viscosity with water)
MODE OF APPLICATION	Brush, Spray or Roller
SHADES AVAILABLE	As per colour charts
COVERAGE	17-19sq meters per litre per coat.
DRYING TIME	Touch dry 15 to 20 minutes
RECOAT TIME	2 hours minimum
FINISH	Smooth & Flat
CLEAN UP THINNER	Water
SURFACE PREPARATION	The surface before painting should be free from dust, dirt, oil, grease, etc. and suitably primed, where required.

PRIMERS RECOMMENDED BEFORE APPLICATION OF THIS PRODUCT

TIMBER & TIMBER PRODUCTS	Wood Primer
HARDBOARDS	Pacific All Purpose Undercoat
CONCRETE, MASONARY, ETC. (dried & cured)	Nil i.e. apply directly without any primer or sealer
NEW CONCRETE BLOCKS	Two coats of Acrylic Block Sealer