

# PACIFIC FAST DRY ACRYLIC SEALER UNDERCOAT

## EXTERIOR / INTERIOR FINISH

### PRODUCTION DESCRIPTION

It is superior quality acrylic emulsion based sealer / undercoat with excellent opacity. It dries fast to allow you the application of Finishing Coat. Make the surface uniform and prepared for the application of next coat.

### AREAS OF APPLICATION

Paper faced plasterboards, fibrous cement boards, concrete, plaster, fibrous cement, concrete blocks.

### TECHNICAL DATA

<b>COLOUR RANGE</b>	White can be tinted to light colours.
<b>GLOSS LEVEL</b>	Flat
<b>SOLVENT RESISTANCE</b>	Alcohol and aromatic hydrocarbons may attack The film.
<b>TOXICITY</b>	Dry film is non-toxic and free
<b>THINNING &amp; CLEAN UP</b>	Water
<b>COVERAGE</b>	12sq.mtr/litre per coat. Practical coverage may depend on surface profile, method of Application and weather conditions.
<b>DRYING TIME (at 25C &amp; RH 60%)</b>	Touch dry : 20 minutes
<b>RECOAT TIME</b>	2 hours
<b>PACK AVAILABLE</b>	20L, 10L, 4L, 1L

### APPLICATION

<b>METHOD OF APPLICATION</b>	Brush, Roller or Spray
<b>SURFACE PREPARATION</b>	Remove all dust, grease, loose and flaking paint by thoroughly cleaning the surface.
<b>APPLICATION</b>	Stir the contents thoroughly before and during. Use with a broad flat stirrer, using an upward Lifting action. Apply one even coat direct from the container. Keep in mind the drying time between coats. On very hot days a little bit of Thinner could be used for ease of application.